

High Flow Ozone Interceptor

High Flow Ambient Ozone Destruct Unit

The *Ozone Interceptor* destroys ozone present in ambient air at high flowrates. This high-flow destruct unit provides an ozone free “blanket” of air around sensitive equipment and can reduce and remove the corrosive oxidant in areas with problematic ozone levels. This device will greatly improve your work efficiency.

Features

- Lightweight and Compact Design
- High Flow Design
- Capable of Continuous Operation
- Plugs Into Standard 110 VAC Wall Outlet
- Greater Than 99% Destruction Efficiency



Product ID: **NT-70**
Lead Time: **7 days**
Price: **\$1,195.00**

Specifications

Flow Rate: 70 CFM
Fan Life: 100,000 Hours
Operation: Continuous or Intermittent - can operate 24-hrs/day 365 days a year
Voltage: 120V/60Hz or 220V/50Hz
Amperage: 0.5 Amp
Efficiency: Greater than 99%
Warranty: 1-year
Size: 20-in x 5-in x 5-in (LxWxH) 51-cm x 13-cm x 13-cm (Handle makes unit 1-in higher for a 6-in overall height)
Weight: 11-lbs (5 kg)

Control View



Simple On/Off Switch and 3 Amp Fuse

Perfect for Microarray facilities and other ozone sensitive equipments.